

The Brief Technical Specifications of the model are as follows

Model	SHAKTIMAAN -35Mx (M&M 275 MKM except sheet metal)	
ENGINE		
Manufacturer	Mahindra & Mahindra Ltd.,	
Engine Model	MDI-1895B3A	
No. of Cylinders/Engine HP (Cat.)	3 / 39	
Displacement (cc) / Rated RPM	2048 / 2100	
Air Cleaner	Oil bath with dry element	
Clutch	Heavy Duty Single Dry Plate	
TRANSMISSION & HYDRAULIC		
Make	Mahindra & Mahindra Ltd.	
Type	M&M -275 MKM , 8 Forward & 2 Reverse with Hi-Low selector lever, Mechanical combination of sliding and constant mesh.	
Power Take Off	Rear Mounted with 6 Splines	
Standard PTO (RPM) at Rated Engine Speed	543	
Steering	Screw & Nut with Re-Circulating Ball	
Brake System	Dry Disc with Heavy duty Brake Liner	
Hydraulic System	Hy-tec, fully live hydraulic system with position & draft control	
Lifting Capacity (kg)	1000	
Tyres - Front	6.00 x 16	
- Rear	12.4 x 28	
Front axle	M&M -265 MKM	
OVER ALL DIMENSIONS OF TRACTOR		
Total Height	2170 ± 20	
Total Length	3440 ± 20	
Total Width	1715 ± 20	
Wheel Base	1880 ± 20	
Ground Clearance	350 ± 10	
WEIGHTS		
Total Weight Kg. (Ballasted)	2670 ± 50	
Total Weight Kg. (un Ballasted)	1790 ± 50	
Tractor speeds (kmph)	Speed Range	
Forward	2.8 to 28	
Reverse	4.2 to 12.3	
NOTE:-As per company's policy of continuous improvement, The specification given are subject to change from time to time without prior notice.		